JANOME CoverPro 3000 Professional



SPECIALTY SERIES

CoverPro 3000



PROFESSIONAL

Standard accessories



Optional accessories:

- Hem guide type 1 795803109
 Hem guide type 2 795839104
- Adjustable seam guide 795806102
- Elastic gathering attachments Narrow 6-8.5mm – 795816105 Wide 9-13.5mm - 795817106
- Centre guide Foot 795819108 • Tape binder (32-8mm) – 795838103
- Tape binder (42-12mm) 795844009
- Tape binder (50-15mm) 795845000
- Extra wide table 795812008
- Needles ELx705 #12/80 795807103
- Needles ELx705 #14/90 795808104

Machine size (mm)W412 × H335 × D245Machine weight (kg)8.6kgBed typeFlat bed with convertible free-armWorkspace (to right of needles)Width 143mm x height 100mmLightingLED (ErP) in 3 locations including retractable sewing lightTop cover stitch functionBuilt-in retractable top cover stitch guide with spreaderStitch typesTop Cover Stitch: 3 needle, 5 thread 2 needle, 4 thread Cover Stitch: 1 needle, 2 thread 2 needle, 4 thread Cover Stitch: 1 needle, 2 thread 2 needle, 4 thread Cover Stitch: 1 needle, 2 threadFine mode switching leverFine: lightweight fabrics STD: standard to heavier weight fabrics STD: standard to heavier weight fabricsNumber of needlesUse with 3, 2 or 1 needleNumber of needlesStitch with 5/4/3/2 threadsStitch width using 3 needles Stitch width using 3 needles Stitch width using 3 needles four (Standard), 3mm (narrow)Stitch length (mm)1.0 - 4.0Differential feed ratio0.5 - 2.25Feed dog8 pcsColour coded threadingYes, acjusting screw on top cover of machinePresser foot pressure adjustment furead tension release deviceNanuolThread tension release deviceRaise presser foot to release tensionsCarrying handleShort handle folds away in top cover of machineFuread tension release deviceShort handle folds away in top cover of machineFuread tension release deviceShort handle folds away in top cover of machineFace dongShort handle folds away in top cover of machineFuread te		
Bed typeFlat bed with convertible free-armWorkspace (to right of needles)Width 143mm x height 100mmLightingLE(FP) in 3 locations including retractable sewing lightTop cover stitch functionBuill-in retractable top cover stitch guide with spreaderStitch typesTop Cover Stitch: 3 needle, 5 thread 2 needle, 4 thread Cover Stitch: 2 needle, 1 threadMumber of needle(s)Elx705 Size 12/80 or 14/90Number of threads0.5 - 2.25Stitch width using 3 needles Stitch width using 4 needlesSimm (standard), 3mm (narrow)Stitch width using 4 needlesSimm (standard), 3mm (narrow)Stitch width using 5 needles Stitch width using 6 needlesSimm (standard), 3mm (narrow)Stitch width using 6 needles Stitch width using 6 needlesSimm (standard), 3mm (narrow)Stitch width using 6 needles Stitch width using 6 needlesSimm (standard)	Machine size (mm)	W412 × H335 × D245
NoticeWidth 143mm x height 100mmLightingKidth 143mm x height 100mmTop cover stitch functionBuilt-in retractable sewing lightStitch typesTop Cover Stitch: 3 needle, 4 thread 2 needle, 4 thread Chain Stitch: 1 needle, 4 thread Chain Stitch: 1 needle, 4 thread Chain Stitch: 1 needle, 2 thread C	Machine weight (kg)	8.6kg
LightingLED (ErP) in 3 locations including retractable sewing lightTop cover stitch functionBuilt-in retractable top cover stitch guide with spreaderStitch typesTop Cover Stitch: 3 needle, 5 thread 2 needle, 4 thread Triple Cover Stitch: 3 needle, 5 thread 2 needle, 4 thread Cover Stitch: 1 needle, 2 thread Chain Stitch: 1 needle, 2 threadFine mode switching leverFine: lightweight fabrics STD: standard to heavier weight fabricsNeedle threaderBuilt-in with needle selection sliderMaximum speed (spm)1.000 stitches per minuteType of needle(s)ELx705 Size 12/80 or 14/90Number of needlesStitch with 5/4/3/2 threadsStitch width using 3 needles stitch width using 2 needlesform (3mm + 3mm between needles) smm (standard), 3mm (narrow)Stitch length (mm)1.0 – 4.0Differential feed ratio0.5 – 2.25Feed dogB pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverFresser foot pressure adjustmentManualThread tension release deviceSnap-on/offThread tension release deviceShort handle folds away in top cover of machineCarrying handleSoft vinyl dust coverMachine coverSoft vinyl dust coverFoot controlTrica (No heat)	Bed type	Flat bed with convertible free-arm
retractable sewing lightTop cover stitch functionBuilt-in retractable top cover stitch guide with spreaderStitch typesTop Cover Stitch: 3 needle, 5 thread 2 needle, 4 thread Cover Stitch: 1 needle, 2 thread Cover Stitch: 1 needle, 2 thread Cover Stitch: 1 needle, 2 threadFine mode switching leverFine: lightweight fabrics StD: standard to heavier weight fabricsNeedle threaderBuilt-in with needle selection sliderMaximum speed (spm)1.000 stitches per minuteType of needle(s)Use with 3, 2 or 1 needleNumber of needlesStitch with s/4/3/2 threadsStitch width using 3 needles stitch width using 2 needles6mm (3mm + 3mm between needles) omm (standard), 3mm (narrow)Stitch length (mm)1.0 - 4.0Differential feed ratio0.5 - 2.25Feed dogB pcsColour coded threadingTo left of needles on side of machinePresser foot pressure adjustment Chared tension release deviceYes, adjusting screw on top cover of machinePresser foot pressure adjustment Carrying handleSoft vinyl dust coverMachine coverSoft vinyl dust coverMachine coverSoft vinyl dust cover	Workspace (to right of needles)	Width 143mm x height 100mm
Jet of the speed speed speed of the speed s	Lighting	
Sinch types2 needle, 4 thread Triple Cover Stitch: 3 needle, 4 thread Cover Stitch: 2 needle, 3 thread Chain Stitch: 1 needle, 2 threadFine mode switching leverFine: lightweight fabrics STD: standard to heavier weight fabricsNeedle threaderBuilt-in with needle selection sliderMaximum speed (spm)1,000 stitches per minuteType of needle(s)ELx705 Size 12/80 or 14/90Number of needlesUse with 3, 2 or 1 needleNumber of threadsStitch with 5/4/3/2 threadsStitch width using 3 needles Stitch width using 2 needlesGmm (3mm + 3mm between needles) smm (standard), 3mm (narrow)Stitch length (mm)1.0 – 4.0Differential feed ratio0.5 – 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper cover of machinePresser foot pressure adjustmentYes, adjusting screw on top cover of machinePresser foot changeShort handle folds away in top coverThread tension release deviceRaise presser foot to release tensions Carrying handleKachine coverSoft vinyl dust coverFoot controlTriac (No heat)	Top cover stitch function	
STD: standard to heavier weight fabricsNeedle threaderBuilt-in with needle selection sliderMaximum speed (spm)1,000 stitches per minuteType of needle(s)ELx705 Size 12/80 or 14/90Number of needlesUse with 3, 2 or 1 needleNumber of threadsStitch with 5/4/3/2 threadsStitch width using 3 needles Stitch width using 2 needlesdom (standard), 3mm (narrow)Stitch length (mm)1.0 - 4.0Differential feed ratio0.5 - 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustment Thread tension adjustmentManualThread tension release device Machine coverShort handle folds away in top cover of mrachMachine coverShort handle folds away in top cover Triac (No heat)	Stitch types	2 needle, 4 thread Triple Cover Stitch: 3 needle, 4 thread Cover Stitch: 2 needle, 3 thread
Maximum speed (spm)1.000 stitches per minuteType of needle(s)ELx705 Size 12/80 or 14/90Number of needlesUse with 3, 2 or 1 needleNumber of threadsStitch with 5/4/3/2 threadsStitch width using 3 needles Stitch width using 2 needles6mm (3mm + 3mm between needles) omm (standard), 3mm (narrow)Stitch length (mm)1.0 – 4.0Differential feed ratio0.5 – 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustment Thread tension adjustmentManualThread tension release device Machine coverShort handle folds away in top cover Short handle folds away in top cover 	Fine mode switching lever	
Type of needle(s)ELx705 Size 12/80 or 14/90Number of needlesUse with 3, 2 or 1 needleNumber of threadsStitch with 5/4/3/2 threadsStitch width using 3 needles Stitch width using 2 needlesomm (3mm + 3mm between needles) omm (standard), 3mm (narrow)Stitch length (mm)1.0 - 4.0Differential feed ratio0.5 - 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentXes, adjusting screw on top cover of machineThread tension release deviceRaise presser foot to release tensions Short handle folds away in top cover fract (No heat)Machine coverSoft vinyl dust coverFoot controlTriac (No heat)	Needle threader	Built-in with needle selection slider
Number of needlesUse with 3, 2 or 1 needleNumber of hreadsStitch with 5/4/3/2 threadsStitch width using 3 needles Stitch width using 2 needlesdomm (3mm + 3mm between needles) dmm (standard), 3mm (narrow)Stitch length (mm)1.0 – 4.0Differential feed ratio0.5 – 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentManualThread tension adjustmentManualThread tension release deviceShort handle folds away in top cover of machineMachine coverSoft vinyl dust coverFoot controlTriac (No heat)	Maximum speed (spm)	1,000 stitches per minute
Number of threadsStitch with 5/4/3/2 threadsStitch width using 3 needles Stitch width using 2 needlesform (3mm + 3mm between needles) form (standard), 3mm (narrow)Stitch length (mm)1.0 - 4.0Differential feed ratio0.5 - 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentManualThread tension adjustmentManualThread tension release deviceShort handle folds away in top cover foot nandleMachine coverShort handle folds away in top cover friac (No heat)Foot controlTriac (No heat)	Type of needle(s)	ELx705 Size 12/80 or 14/90
Stitch width using 3 needles Stitch width using 2 needlesGmm (3mm + 3mm between needles) dmm (standard), 3mm (narrow)Stitch length (mm)1.0 - 4.0Differential feed ratio0.5 - 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentYes, adjusting screw on top cover of machineThread tension adjustmentManualThread tension release deviceShort handle folds away in top cover of machineMachine coverSoft vinyl dust coverFoot controlTriac (No heat)	Number of needles	Use with 3, 2 or 1 needle
Stitch width using 2 needles6mm (standard), 3mm (narrow)Stitch length (mm)1.0 - 4.0Differential feed ratio0.5 - 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentYes, adjusting screw on top cover of machineThread tension adjustmentManualThread tension release deviceShort handle folds away in top cover short handle folds away in top coverMachine coverSoft vinyl dust coverFoot controlTriac (No heat)	Number of threads	Stitch with 5/4/3/2 threads
Differential feed ratio0.5 - 2.25Feed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentYes, adjusting screw on top cover of machinePresser foot changeSnap-on/offThread tension adjustmentManualThread tension release deviceRaise presser foot to release tensionsCarrying handleShort handle folds away in top cover of triac (No heat)Foot controlTriac (No heat)		
Feed dog8 pcsFeed dog8 pcsColour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentYes, adjusting screw on top cover of machinePresser foot changeSnap-on/offThread tension adjustmentManualThread tension release deviceRaise presser foot to release tensionsCarrying handleShort handle folds away in top cover of machineMachine coverSoft vinyl dust coverFoot controlTriac (No heat)	Stitch length (mm)	1.0 - 4.0
Colour coded threadingThreading chart and stitch reference chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentYes, adjusting screw on top cover of machinePresser foot changeSnap-on/offThread tension adjustmentManualThread tension release deviceRaise presser foot to release tensionsCarrying handleShort handle folds away in top cover Soft vinyl dust coverFoot controlTriac (No heat)	Differential feed ratio	0.5 – 2.25
Chart located inside looper coverThread cutterTo left of needles on side of machinePresser foot pressure adjustmentYes, adjusting screw on top cover of machinePresser foot changeSnap-on/offThread tension adjustmentManualThread tension release deviceRaise presser foot to release tensionsCarrying handleShort handle folds away in top coverMachine coverSoft vinyl dust coverFoot controlTriac (No heat)	Feed dog	8 pcs
Presser foot pressure adjustment Yes, adjusting screw on top cover of machine Presser foot change Snap-on/off Thread tension adjustment Manual Thread tension release device Raise presser foot to release tensions Carrying handle Short handle folds away in top cover Machine cover Soft vinyl dust cover Foot control Triac (No heat)	Colour coded threading	
Presser foot changeof machinePresser foot changeSnap-on/offThread tension adjustmentManualThread tension release deviceRaise presser foot to release tensionsCarrying handleShort handle folds away in top coverMachine coverSoft vinyl dust coverFoot controlTriac (No heat)Induced tension adjustmentSee link to the CoverPro 3000P on the Janome website.	Thread cutter	To left of needles on side of machine
Thread tension adjustment Manual Thread tension release device Raise presser foot to release tensions Carrying handle Short handle folds away in top cover Machine cover Soft vinyl dust cover Foot control Triac (No heat) Inclusional idea See link to the CoverPro 3000P on the Janome website.	Presser foot pressure adjustment	
Thread tension release device Raise presser foot to release tensions Carrying handle Short handle folds away in top cover Machine cover Soft vinyl dust cover Foot control Triac (No heat) Indexediate See link to the CoverPro 3000P on the Janome website.	Presser foot change	Snap-on/off
Carrying handle Short handle folds away in top cover Machine cover Soft vinyl dust cover Foot control Triac (No heat) Inclusional video See link to the CoverPro 3000P on the Janome website.	Thread tension adjustment	Manual
Machine cover Soft vinyl dust cover Foot control Triac (No heat) See link to the CoverPro 3000P on the Janome website.	Thread tension release device	Raise presser foot to release tensions
Foot control Triac (No heat) See link to the CoverPro 3000P on the Janome website.	Carrying handle	Short handle folds away in top cover
See link to the CoverPro 3000P on the Janome website.	Machine cover	Soft vinyl dust cover
Instructional video See link to the CoverPro 3000P on the Janome website. (Choose from the options below to visit the website.)	Foot control	Triac (No heat)
	Instructional video	See link to the CoverPro 3000P on the Janome website. (Choose from the options below to visit the website.)











AVAILABLE FROM YOUR EXPERT JANOME RETAILER:

Built-in top cover stitch guide

Setting machine for top cover stitch is so quick. The top cover stitch guide and spreader are built-in. Using one finger, simply push down the built-in top cover stitch guide and spreader into position. When finished, simply press the lever to retract and store away. A Janome innovation and time saving feature.

Fine mode switching lever

It's so easy to sew fine weight fabrics. Switch the lever to FINE, machine adjusts ready to stitch light weight fine knits or light weight woven fabrics. Use the STD setting for stitching standard to heavier knit fabrics/woven fabrics. A Janome innovation and time saving feature.

Built-in needle threader

3 needles to thread, use the built-in needle threader, it's easy to use and a time saver. Select the needle for threading by simply sliding the needle threader switch lever to R/M/L (right needle, middle needle, left needle), then push down on the needle threader lever and thread needle. You'll be ready to sew in no time.

Thread chain-off

Top cover stitch and triple cover stitch can chain-off to finish, similar thread chain-off as an overlocker. Depending on the sewing project, finishing options are pulling the needle threads, trim them then pull out behind the needle plate or chain-off leaving a chained thread tail.

Retractable sewing light

LED Lighting in 3 locations, includes the retractable sewing light, which pulls out to illuminate the needle area. The retractable sewing light is an inherited feature from our high-end professional sewing machines. The additional retractable lighting allows you to easily sew at anytime.

www.janome.com.au Janome New Zealand Ltd. PO Box 447, Drury, Auckland 2247 www.janome.co.nz

PO Box 1383, Moorabbin 3189 Victoria

Janome Australia Pty Ltd.